

GalvKleen Paste



DESCRIPTION

A one component, liquid/paste - detergent & abrasive mixture

INTENDED USE

A ready to use, Red tinted mixture used to clean galvanized iron

PRODUCT FEATURES

- Emulsifies with water to give a 'water-break-free' surface after rinsing with drinking quality water
- Acid free and safe to use
- Red tint allows user to see how much is being applied

LIMITATIONS

- Take care to remove all pigmented paste from the surfaces. Do not over-paint residual cleaner.
- In hot weather clean small sections of the surfaces at a time to avoid drying out.

PACKAGING

- 5lt and 20lt

APPEARANCE



Red Oxide coloured Opaque Liquid

CLEANER


- Water

HEALTH AND SAFETY

- This product must be used with caution
- Protective clothing must be worn to protect the user from accidental skin and eye contact
- If the product comes into contact with the skin, wash immediately with lukewarm water and soap, if the eyes are affected, flush with water of diluted boric acid solution and seek medical attention immediately
- Non flammable
- Avoid inhalation of vapours by wearing a mask with chemical filter
- Refer to the Material Safety Data Sheet (MSDS)

APPLICATION

- *GalvKleen Paste* requires stirring with a flat-bottomed paddle prior to use.
- Stir well until the paste is uniform
- Do not dilute paste for use
- Remove any gross dirt and contamination by mechanical means or high pressure water blasting

	<p>Apply the GalvKleen to the surface and abrade thoroughly with a Scotchbrite pad</p>
--	--

- Rinse off quickly, do not allow the paste to dry out
- Dry the surface as quickly as possible in preparation for painting which should be applied as soon as possible to prevent re-oxidisation

STORAGE & HANDLING

- Store at temperatures between 5°C and 40°C

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 14/10/2010**