

# Hydrosolve



## DESCRIPTION

A one component, water – detergent – solvent based degreaser

## INTENDED USE

A ready to use, blue coloured degreaser that quickly dissolves grease off all surfaces

## PRODUCT FEATURES

- Used to degrease components prior to painting
- Will remove mineral oils, cutting oils and light greases from the surfaces
- Safe to use in the home or garage for all small degreasing jobs
- Any metal objects and previously painted aged coatings can be degreased using **Hydrosolve**
- Will lift freshly painted enamels and undercoats
- V.O.C. 630 grams per litre

## LIMITATIONS

- Not suitable for solvent sensitive surfaces
- Dispose of run-off in an environmentally approved way

## PACKAGING

- 5lt and 20lt

## APPEARANCE



Blue opaque liquid

## CLEANER


- Water

## HEALTH AND SAFETY

- This product must be used with caution
- Protective clothing must be worn to protect the user from accidental skin and eye contact
- If the product comes into contact with the skin, wash immediately with lukewarm water and soap, if the eyes are affected, flush with water of diluted boric acid solution and seek medical attention immediately
- Non flammable
- Avoid inhalation of vapours by wearing a mask with chemical filter
- Refer to the Material Safety Data Sheet (MSDS)

## APPLICATION

- **Hydrosolve** is ready for use and does not require mixing
- Remove any gross dirt and contamination by mechanical means or high pressure water blasting

 Brushes	Apply the Hydrosolve to the surface and work in with a brush
--	--

- Leave for 2-3 minutes and wash off with drinking quality water and allow drying as soon as possible
- Heavier contaminations will require several repeated applications to render the surface clean for painting
- Rinsing with HOT WATER is more effective

## STORAGE & HANDLING

- Store at temperatures between 5°C and 40°C

## DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 10/10/2011**