

Powafix Acrylic Sealant



DESCRIPTION

Powafix All Purpose Acrylic Sealant provides excellent adhesion to most surfaces. Its long lasting flexibility allows continuous expansion and contraction without cracking or shrinking.

RECOMMENDED USES

- For joining & sealing a variety of building materials & construction elements that are likely to undergo moderate movement
- Suitable for interior & Exterior use
- Repairs cracks in walls, skirting boards, doors & windows
- Seals between plaster board panels, ceiling boards, cornices & decorative ceiling panels

SURFACE PREPARATION

- Remove loose & flaking paint or foreign material
- Clean surfaces with Powafix Sugar Soap

APPLICATION

- Cut nozzle at an angle & insert into caulking gun
- Extrude continuously on a steady line over affected area
- Tool off excess sealant within 5 minutes or before drying. Smooth off with water, does not require sanding.
- Paintable in 10 minutes. Can be coated with water & solvent based products

PACKAGING

- 260ml Cartridge

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Not recommended for areas in frequent or prolonged contact with water
- 7 day drying time is require if coating with solvent based paint
- Store in a cool dry place
- Avoid contact with skin

ASSOCIATED PRODUCTS

- Powafix Sugar Soap

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**