

Powafix

All Purpose Crackfiller



DESCRIPTION

All Purpose Crackfiller is a tough filler formulated with a unique blend of cement and plaster to provide a weather resistant and flexible surface for both interior and exterior applications.

RECOMMENDED USES

- All Purpose Seals, fills cracks & Holes in materials such as plaster, concrete, brick, stone & Asbestos fire board, etc.
- To fill gaps around door and window frames & to replace loose mortar

SURFACE PREPARATION

- Open up all cracks to ensure good adhesion to all surfaces
- All surfaces to be filled must be free of loose particles, dust, grease & oil. Cover all nails & Screw heads with universal Undercoat

APPLICATION

- Add 2 parts All Purpose Crackfiller to 1 part water & mix thoroughly
- Stir well to a smooth paste
- Allow to stand 5 minutes before using
- Remains workable for 1 hour
- Deep cavities must be filled in two or more stages to allow for thorough drying
- Use a wet putty knife blade to smooth off the surface
- Allow to dry for 2-4 hours before sanding
- Sand smooth with a medium grit sand paper
- Prime repaired area with a suitable solvent based plaster primer or Speccoats Water Repellent

PACKAGING

- 500g, 2Kg & 10Kg

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Do not apply in thin layers
- Do not use in wet or damp conditions
- Do not use on surfaces regularly under water
- Fold over plastic sachet, place in carton & Close the lid to prevent humidity from hardening the powder

ASSOCIATED PRODUCTS

- Speccoats Universal Undercoat
- Speccoats Phuma Manzi Water Repellent

SAFETY INFORMATION

- Wash hands & equipment with water
- KEEP OUT OF REACH OF CHILDREN

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**