

Powafix

Fill n Fix Ready Mixed Filler



DESCRIPTION

A Powerful interior/exterior ready mixed filler. This fibre reinforced filler repairs crack, holes & blemishes in brock, concrete, plaster, stone, timber & metal surfaces. This water based product provides excellent adhesion and requires no primer.

RECOMMENDED USES

- Can be used as a window putty & as a ceramic tile adhesive
- Can be sanded to an ultra-smooth surface
- Will not shrink into cavity when drying
- Can be painted over with gloss enamels or acrylic PVA's
- Can be thinned with water to make it more work-able

SURFACE PREPARATION

- Open up all cracks to ensure good adhesion to all surfaces
- All surfaces to be filled must be free of loose particles, dust, grease & oil
- Clean all surfaces with Powafix Sugar Soap before applying Fill n' Fix
- Shuttered or moulded concrete must be primed with Alkali Plaster Primer before applying Powafix Fill n' Fix
- Cover all nails & screw heads with Universal Undercoat

APPLICATION

- Apply with a putty knife by pressing the paste firmly into the cavity. Use a wet putty knife to smooth the Fill n Fix down.
- A damp sponge can also be used to smooth off Fill n Fix 10-15minutes after application
- Deep cracks must be filled in 3-5mm layers to ensure thorough drying
- Allow 6 hours before sanding or painting. For solvent based paints allow 2 days
- When set, sand to a smooth finish prior to painting

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Replace the lid firmly to prevent evaporation (if the product stiffens over a period of time, add a few drops of water to soften and make(it work-able)
- Wash hands after use in warm water

ASSOCIATED PRODUCTS

- Powafix Sugar Soap
- Universal Undercoat
- Alkali Plaster Primer

PACKAGING

- 500ml. 1Lt & 5Lt

PACKAGING

- Avoid Contact with eyes
- KEEP OUT OF REACH OF CHILDREN

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**