

Powafix

Interior Crackfiller



DESCRIPTION

Powafix Interior Crackfiller is a highly effective smooth filler for all interior application to repair cracks & holes in plaster, brick, wood, concrete & asbestos fibre Board

SURFACE PREPARATION

- Open up all cracks to ensure good adhesion to all surfaces
- All surfaces to be filled must be free of loose particles, dust, grease & oil
- Cover all nails & screw heads with Universal Undercoat

APPLICATION

- Mix 2 parts Interior Crackfiller to 1 Part water. Allow to stand
- Mix thoroughly to form a smooth paste which should remain workable for about 45 minutes after mixing
- Deep cavities should be filled in layers with a putty knife or trowel in 2 or more stages
- Allow to dry for a minimum of 2-4 hours before sanding
- Sand smooth with a medium grit sandpaper
- Apply Alkali Plaster Primer or Phuma Manzi Water Repellent over the filler prior to painting with either and Acrylic PVA or Enamel paint

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Interior Crackfiller is not recommended for exterior use or damp areas
- Do not apply in very thin layers
- Fold over the plastic sachet & place in the carton. Close the lid to prevent humidity from hardening the powder

ASSOCIATED PRODUCTS

- Phuma Manzi Water Repellent
- Universal Undercoat
- Alkali Plaster Primer

PACKAGING

- 500g, 2Kg & 10Kg

SAFETY INFORMATION

- Wash hand and equipment with water
- KEEP OUT OF REACH OF CHILDREN

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**