

Powafix

Powaskim Superfine



DESCRIPTION

A ready mixed interior/exterior skimming plaster specially formulated for repairing hairline cracks, joints and other surface blemishes. This easy to apply plaster will enhance the decorative finish of any coating and requires no primer

SURFACE PREPARATION

- Remove flaking paint and all loose dust & particles. Clean off grease & oils with Powafix Sugar Sap.
- Sand gloss enamel and other smooth surfaces with a Coarse 100 grit sandpaper to provide a key for Powaskim High Build
- Shuttered or moulded concrete must be primed with Alkali Plaster Primer prior to applying Powaskim High Build
- Cover all nails & Screws with Universal Undercoat

APPLICATION

- Mix thoroughly to a creamy consistency
- Apply with steel trowel in a thin layer, depending on the surface
- Skim 2 or more coats if necessary. Skim thickness should be between 0.5mm-1mm
- Allow 4-8 hours before painting. For enamel overcoat allow 48 hours
- For easy sanding use 100 grit sand paper within 24 hours of application.
- There is no need to overcoat with a plaster primer
- Clean up with water

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Do not use in excessively damp conditions or surfaces regularly under water.
- Keep the lid closed to prevent hardening (can be stored with a small amount of water)

ASSOCIATED PRODUCTS

- Powafix Sugar Soap
- Universal Undercoat
- Alkali Plaster Primer

PACKAGING

- 500ml, 1lt, 5lt, 10lt & 20lt

SAFETY INFORMATION

- Wash hand and equipment with water
- KEEP OUT OF REACH OF CHILDREN

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**