

Powafix

Spackle Smooth



DESCRIPTION

Spackle is ideal for filling small imperfections, blemishes, chips and indentations, spackle provides a smooth white finish and can be used on ceilings, floors, window frames, walls, skirting's & cupboards

SURFACE PREPARATION

- Remove flaking paint and all loose dust & particles. Clean off grease & oils with Powafix Sugar Sap.
- Sand the edges of damage surfaces to remove loose paint and timber splinters, and remove dust
- Cover all nails & Screws with Universal Undercoat

APPLICATION

- Spackle Smooth must be mixed thoroughly before applying
- Apply onto the clean surface with a putty knife or spatula
- Maximum thickness of application to be no more than 1mm-2mm
- Fills deeper than 2mm must be built up gradually with 2mm thick layers of the filler
- Each layer must be thoroughly dry before applying the next
- After approximately 1 hour drying time, sand with a fine grit sandpaper to an ultra-smooth finish before painting
- Drying time is 2 hours

STANDARD COLOUR AVAILABILITY

White



PRECAUTIONS

- Spackles Smooth is not recommended for use in damp areas or areas in contact with water
- This filler must not be diluted
- Keep lid closed when not in use
- Wash hands after use
- Replace lids firmly. Store in a cool dry place out of reach of direct sunlight

ASSOCIATED PRODUCTS

- Powafix Sugar Soap
- Universal Undercoat

PACKAGING

- 250ml plastic tub

SAFETY INFORMATION

- Wash hand and equipment with water
- KEEP OUT OF REACH OF CHILDREN

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 16/03/2011**