

Steel & Plate Degreaser



DESCRIPTION

A one component, solvented degreaser

INTENDED USE

A ready to use, solvented degreaser that quickly dissolves grease and oils off metal surfaces

PRODUCT FEATURES

- Used to degrease metal sheet work prior to painting
- Will remove all mineral oils, cutting oils and light greases from the surfaces leaving the surfaces clean for painting

LIMITATIONS

- Not suitable for solvent sensitive surfaces
- Dispose of run-off in an environmentally approved way
- Grease & oil are soluble in steel and plate degreaser, clean rags must not be re-used

PACKAGING

- 5lt and 20lt

APPEARANCE



Colourless thin Liquid

HEALTH AND SAFETY

- This product must be used with caution
- Protective clothing must be worn to protect the user from accidental skin and eye contact
- If the product comes into contact with the skin, wash immediately with lukewarm water and soap, if the eyes are affected, flush with water of diluted boric acid solution and seek medical attention immediately
- Non flammable
- Avoid inhalation of vapours by wearing a mask with chemical filter
- Refer to the Material Safety Data Sheet (MSDS)

APPLICATION

- *Steel & Plate Degreaser* is ready for use and does not require mixing
- Remove any gross dirt and contamination by mechanical means or high pressure water blasting



Brushes

Apply the Steel & Plate Degreaser to the surface and work in with a brush

- Leave for 2-3 minutes and wipe off with clean rags
- Heavier contaminations with require several repeated applications to render the surface clean for painting
- Rinsing with HOT WATER is more effective

STORAGE & HANDLING

- Store at temperatures between 5°C and 40°C

DISCLAIMER

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product. **ISSUE DATE 15/10/2010**