

AEROCLEAN CITRUS Tar & Wax Remover

SOLVENT BASED

Description:

High performance cleaning agent for tar, wax, oils, grease on various surfaces.

Intended Uses:

Automotive: Removes tar, tree sap, wax, and road grime from car exteriors and undercarriages.

Industrial: Cleans machinery, equipment, and tools from sticky residues like adhesives and wax.

General Cleaning: Suitable for use on a wide range of surfaces including floors, glass, and plastics.

Features & Benefits:

- Powerful citrus-based formula
- Safe for use on automotive paint, glass, plastic, and metal surfaces
- Pleasant citrus scent
- Leaves no residue
- Fast drying.

Certifications:

-

Technical Data:

Smell / Fragrance	Citrus Scent
Product Physical Form	Aerosol
Colour	Clear
Method Of Application	Aerosol Spray
Pack Size	400ml Aerosol Can (12 In A Box)
Storage	Store out of direct sunlight in dry conditions between 15°C and 25°C.
Shelf Life	12 months when stored as recommended in original un-opened containers

Application:



Shake can well before use.



**Hold can 15-20 cm from the surface to be cleaned.
Spray the product directly onto the affected area and**



Allow it to sit for 1-2 minutes.



Wipe away contaminants with a clean cloth or sponge.

NB* For stubborn residues, repeat the process or use a brush to scrub the surface.
Always test in an inconspicuous area before full application on delicate surfaces.

Important Information:

Caution:

Avoid prolonged inhalation of vapours. Use only in a well-ventilated area.
Do not spray towards open flame or heat sources.
Keep out of reach of children.
For external use only, avoid contact with eyes.
Always test on a small inconspicuous area before using on delicate or painted surfaces to ensure compatibility.

Disposal:

Dispose of container and any unused contents in accordance with local regulations.
Do not puncture, incinerate, or expose the container to high temperatures.
Do not discharge into drains or the environment.

Surface Preparation:

In general, the following guidelines for preparation should be adhered to. Always consult for a detailed specification.

Test on a Small Area:

Always test the product on a small, inconspicuous area before full application to ensure compatibility with the surface, particularly on delicate or painted surfaces.

Surface Temperature:

For optimal results, apply the remover when the surface is at room temperature (between 5°C and 25°C). Avoid using on surfaces that are extremely cold or hot.

Protection:

If applying to sensitive or painted surfaces, ensure they are adequately protected to prevent any potential damage from excess product contact.

Systems:

Consult with Specialized Coating System for application specific recommendations.

Safety Information:

- Refer to product SDS for health & safety prior to using products.
- Always wear safety clothing / protection. Respirators, eye protection and skin protection.
- Apply in well-ventilated areas.