

AEROMARK® STENCIL

INTERIOR & EXTERIOR

SOLVENT BASED

Description:

A solvent based, fast drying, modified nitrocellulose, stencil marking aerosol spray paint.

Intended Uses:

AEROMARK® Stencil is a high-performance marking paint designed to produce sharp, precise and highly visible markings. Ideal for use with stencils to deliver crisp, clean edges with minimal bleed.

This aerosol's fast drying properties & excellent coverage allows for fast marking application and is ideal for enhancing the visibility of safety markings, instructions, and hazards identification in the workplace.

Features & Benefits:

- Fast Drying – Reduces downtime and allows for quicker handling.
- Excellent Line Definition – Delivers crisp, clean edges with minimal bleed when used with stencils.
- Versatile Application – Can be used on a variety of substrates.
- Excellent Smoothness & Appearance
- Good Abrasion Resistance

Certifications:

-

Technical Data:

Product Physical Form	Aerosol
Binder Type	Modified nitrocellulose
Colour	RAL 1003 Signal Yellow, RAL 1026 Luminous yellow, RAL 2007 Luminous Orange, RAL 3001 Signal Red, RAL 4007 Purple Violet, RAL 6032 Signal Green, RAL 9017 Signal Black
Appearance	Smooth Satin
Recommended WFT	TBC – TBC µm per coat
Recommended DFT	TBC – TBC µm per coat
Spreading Rate	TBC – TBC m ² / Litre per can
Number of Coats	1 - 2
Method of Application	Aerosol Spray
Pack Size	400 ml (12 x cans per box)
Storage	Store out of direct sunlight in dry conditions between 15°C and 25°C
Shelf Life	12 months when stored as recommended in original un-opened containers

Important Information:

- Always consider a test patch to check suitability & adhesion.
- Technical & application data herein is for the purpose of establishing a general guideline of the coating application procedure.
- Test performance results were obtained in a controlled laboratory environment and Specialized Coating Systems makes no claim that the exhibited published test results, or any other tests, accurately represent results found in all field environments. As application, environmental and design factors can vary, due care should be exercised in the selection & verification of the performance and use of the coating.

AEROSOLS: AEROMARK®

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product

- Always check weather forecast before painting. Do not paint if rain fall is imminent as it will negatively affect the ability of the product to cure and bond to the surface.


Surface Preparation:

In general, the following guidelines for preparation should be adhered to. Always consult for a detailed specification.

- The areas to be coated should be dry, firm, solid and free from dust, oil, fats, and other contaminants.
- Oil can be removed using **AEROCLEAN HEAVY DUTY Degreaser**.
- Fungal growth or algae can be removed using **Fungicidal Wash**.
- Laitance and loose particles must be removed thoroughly i.e., grinding /high pressure cleaning.
- Moisture content of concrete surfaces should not exceed 4%.
- After the cleaning process & before application of the primer coat, it's important that surfaces have been allowed the proper drying time.

Substrate	Cleaner	Primer
Metal	Clean with AEROCLEAN® HEAVY DUTY Degreaser . Remove any rust by coarse sanding or with bristle brushes.	AEROPRIME® Universal Primer or AEROPRIME® Epoxy Primer
Plastic	Clean with AEROCLEAN® HEAVY DUTY Degreaser	AEROPRIME® Plastic Primer
Polystyrene	Wipe surface down with a dry cloth, ensure there is no dust or contaminants on the surface	AEROPRIME® Polystyrene Primer
Wood	Lightly sand surface	No primer required

Application:



After use, invert & spray until paint clears. An adhesion test sample should always be carried out. Use primer where required.

Application Environment			
	Surface Temperature	Ambient Temperature	Relative Humidity
Minimum	10°C	15°C	No Lower Limit
Maximum	35°C	45°C	85%

* or 3°C above dew point

Drying & Overcoating Information	
Touch Dry	15 min @ 25°C
Overcoating Time	6 hours @ 25°C
Hard Dry	24 hours @ 25°C
Extra Information	-

AEROSOLS: AEROMARK®

Page 2 of 3

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product

Latest Update:
14/07/2025
Issue Date:
14/07/2025

Systems:

Consult with Specialized Coating System for application specific recommendations.

Safety Information:

- Refer to product SDS for health & safety prior to using products.
- Always wear safety clothing / protection. Respirators, eye protection and skin protection.
- Apply in well-ventilated areas.

AEROSOLS: AEROMARK®

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product