

AEROTECH® S-LUBE Multi-purpose

Oil based, Silicone-Free aerosol spray.

Intended Uses:

AEROTECH® S-LUBE Multi-purpose, A high-performance, oil-based multi-purpose lubricant designed for penetration, long-lasting lubrication, rust protection, and water displacement.

It effectively loosens seized components, eliminates squeaks, and provides a protective barrier against moisture, corrosion, and environmental contaminants, lubricates machinery, tools, and moving parts, reducing wear and friction, protects engine components, nuts, bolts, hinges, and locks from rust and corrosion, Ideal for door hinges, locks, garden tools, and general-purpose lubrication.

Suitable for a wide range of applications in industrial, automotive, and household maintenance.

Properties:

- Base Composition: Oil-based formulation
- Lubrication: Long-lasting, smooth performance
- Penetration: Loosens rusted, corroded, or seized metal parts
- Rust Protection: Forms a protective barrier against oxidation and corrosion
- Water Displacement: Effectively repels moisture and prevents short circuits

Technical Data:

Colour	Transparent
Method of Application	Aerosol spray
Pack Size	400ml (12 per carton)
Density @ 15°C – ASTM D1298	0.985 kg / lt
Viscosity @ 20°C – ASTM D445	17 cSt
Flash Point °C – ASTM D93	130

Limitations :

- Technical and application data herein is for the purpose of establishing a general guideline of the coating application procedures.
- Test performance results were obtained in a controlled laboratory environment and Specialized Coating Systems makes no claim that the exhibited published test results, or any other tests, accurately represent results found in all field environments. As application, environmental and design factors can vary, due care should be exercised in the selection and verification of the performance and use of the coating.

Storage:

- Shelf Life: 12 months at 25°C from date of manufacture. Subject to inspection thereafter.
- Store in dry conditions out of direct sunlight away from sources of heat or ignition.
- Store at temperatures between 5°C and 35°C.

Precautions:

For complete safety and handling information please refer to the appropriate Safety Data Sheets prior to using this product.