



Decorà



1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Decorative paint with white flakes which give an antique looking finish suitable for interior environments, it allows you to obtain a dark bright slightly rough and at the same time soft finish because of the white flakes in the paint. Decorà is washable after approximately three weeks of application, non-flammable and guarantees good permeability to the watery vapor. These are the characteristics which make Decorà particularly suitable as an indispensable element of furnishings in ancient style environments such as hotels public offices etc.

2.COMPOSITION

Titanium dioxide, an emulsion of acrylic copolymers, special non-toxic additives. It is free from harmful substances such as solvents and pigments containing lead or chrome

3.METHODS OF APPLICATION

Preparation of the surface, sandpaper, dust, putty eventual imperfections with STUCCOMURO or POLISTUCK (in order to obtain a very fine even surface.), and apply one coat of UNIVERSAL FISSATIVO opportunely diluted with water in relationship 1:5 until to 1:10 based on the absorption of the support. leave to dry at least 4 hours and apply one or two coats of PRIMER S (see Tec. Data sheet) opportunely diluted allowing 4-5 hours for drying between each coat. Application, apply DECORA with a wool glove

or paint-brush in circular movements not continuous, in way to evidence the cloudy effect. After approximately 15 minutes it is advisable to proceed in the finishing phase by going back over the applied surface with the DECORA glove in order slightly press in any flakes which might stick out.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1030 + / - 30 g/Lt.

FILM APPEARANCE: Matt. (not shiny)

COLOURS: to be chosen in the catalogue(obtainable also with ARTHE CONCENTRATO or our GLOBAL TINTING SYSTEM)

VISCOSITY: thixotropic.

YIELD: 7-8 m²/Lt.

TEMPERATURE OF APPLICATION: between 10°C and 30 °C.

DILUTION: ready to use.

PACKAGE: Lt. 4 polyethylene containers.

DRYING: dry to the touch: 4-5 at hours. Completely dry: 24-48 hours at 20°C.

APPLICATION: Brush or wool Glove.

PRESERVATION: 24 months in the intact packages, away from temperature changes.

HS-CODE: 32091000.

ITEM OF SPECIFICATIONS

Decoration and protection of wall surfaces decorative painting flocculate antique effect, the type DECORA 'of Spiver LTD, Based on titanium dioxide, an emulsion of acrylic copolymers, special non-toxic additives, after suitable

treatment of the support. Price includes materials and implementation, excluding the scaffolding sqm. €

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.



Emotion with paint ...



Specialized Coating Systems (Pty) Ltd
2 Jones Rd, Bartlett AH, Boksburg, Gauteng, South Africa
Tel: 086 137 2468 | Email: enquiries@speccoats.co.za
www.speccoats.co.za