

PATCHING COMPOUND® ReadyMix Skim Coat (Interior)

Ready to Use, DIY filler and skimming compound for interior use

A one component, water based acrylic filler and skimming compound for interior surfaces both new and old

Intended uses

Designed as a ready-to-use interior filler and skimming compound for most building surfaces including walls & ceilings to render surfaces completely smooth prior to painting.

Applied directly cement plasters, concrete surfaces, gypsum board and previously painted surfaces.

Properties

- Easy application
- Excellent sanding properties
- Vapour permeable
- Superior smooth surface
- High coverage / obliteration over dark surfaces
- Excellent overcoatability

Technical Data

Composition	Water based Acrylic putty with specially graded fillers
Colour & Appearance	Brilliant White
Pack Size	5, 25Kg Buckets 25Kg Flexi-Bag
Density kg / Lt	1.60 Kg /Lt
Dilution	With Water if required
Coverage	0.5 to 3.2 kg / m ²
Thickness	Up to 2mm maximum / layer
Storage	Store out of direct sunlight in dry conditions between 15°C and 25 °C
Shelf Life	12 months when stored as recommended in original un-opened containers
Clean Up	Water

Surface Preparation

In general, the following guidelines for preparation should be adhered to, always consult for a detailed specification.

- The areas to be coated should be dry, firm, solid and free from dust, oil, fats, and other contaminants.
- Surface must be free of any fungal growth or algae, clean with Fungicidal Wash.
- Laitance and loose particles must be removed thoroughly i.e. grinding /high pressure cleaning.
- Highly porous cement surfaces should be primed with Deep Penetrating Primer or SIMPLY Acrylic Sealer prior to application.

Architectural & Decorative Coatings

Whilst we endeavour to ensure that all advice we give about the product is correct, the information given in this data sheet is not intended to be exhaustive and any person using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so entirely at his own risk. As conditions of use, method of application and suitability of the substrate prior to painting are beyond our control, no guarantee is implied by the recommendations contained herein. We therefore do not accept any liability whatsoever or howsoever arising from the performance of this product or for any loss or damage arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and ongoing product development programmes. It is the user's responsibility to ensure that this sheet is current prior to using the product

Mixing:

Mix well before use

Application:

Apply in an even thin layer. Should higher thicknesses be required it should be done in multiple layers with thorough drying between layers.

After drying the surface can be sanded lightly prior to painting.

Surface should be allowed to dry for 24 hours before application of any paint.

Caution:

- Always consult with technical department if unsure.
- Refer to product MSDS for health & safety prior to using products.
- Always wear safety clothing / protection. Respirators, eye protection and skin protection.

Systems:

Consult with Specialized Coating System for application specific recommendations.