



Rust Style



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Prestigious finishing of top class decoration for interiors oxide effect .It allows you to obtain, with a very easy application, a unique result of extraordinary beauty. RUST STYLE is particularly suitable in typical modern environments, which require refined elegance, sites both in public places and private homes. RUST STYLE is washable after about three weeks of application, non-flammable and provides good water vapour permeability.

2.COMPOSITION

Organic and Inorganic pigments, acrylic copolymer emulsion, special non –toxic additives. Free from harmful substances such as solvents and pigments containing lead and chrome.

3.METHOD OF APPLICATION

Surface preparation.

Sandpaper, dust, cover any imperfections with STUCCOMURO, and apply a coat of FISSATIVO UNIVERSAL diluted with water in the ratio of 1: 5 to 1:10 depending on the surface absorption. Allow drying for at least 4 hours and applying two coats of PRIMER S tint Z-90, between each coat and the other minimum 4-5 hours.

Preparation of the compound

An additive of 70 ml. from ARTHE CONCENTRATE of the chosen colour, and in the case of the SILVER or GOLD colour add 250 ml. of ARTHE PEARL SILVER PEARL ARTHE or K-GOLD, in 2.5 Lt. of RUST STYLE, mix slowly and manually everything and the product will be ready to use (the compound has a poot-life of about 15 days)

Application

Apply RUST STYLE with a special DECORA' SPALTER, by making irregular movements on the surface, like crossed brushstrokes, wait about 20 minutes and start giving the first pressure with a stainless steel trowel on the surface. After about 10 minutes complete, with a stainless steel trowel, paying attention of repeating the same movements of the previous phase.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,020 kg/Lt +/-5%.

PACKAGE: Polyethylene containers Lt. 2,5.

MIXING RATIO: (for silver or gold) RUST STYLE Lt.2,5 and ARTHE PERLA ml.250.

VISCOSITY: Thixotropic aspect.

YIELD: About 10 m²/Lt.

APPLICATION TEMPERATURE: Between 8°C and 30°C.

FILM ASPECT: MATT (not shiny).

DILUTION: Ready to use (Do not dilute).

PACKAGE: Polyethylene containers Lt. 2.5.

DRYING: To dry 4-5h , incompletely 24-48h a 20°C

APPLICATION By brush, finishing touch with a stainless steel trowel.

PRESERVATION: 24 months in the intact packages, away from Temperature changes

5. ITEM OF SPECIFICATIONS

Decoration and protection of interior wall surfaces with decorative effect oxide, RUST STYLE Spiver Ltd. , Based on inorganic and organic pigments, acrylic copolymers in emulsion, special non-toxic additives, after suitable treatment of the surface with PRIMER S colour indicated in the folder.

Price includes materials and implementation, excluding the scaffolding sqm. €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product qual



Emotion with paint ...



Specialized Coating Systems (Pty) Ltd
2 Jones Rd, Bartlett AH, Boksburg, Gauteng, South Africa
Tel: 086 137 2468 | Email: enquiries@speccoats.co.za
www.speccoats.co.za